

FULLY AUTOMATIC PROGRAMMABLE SINGLE KNIFE CUTTING MACHINE



FEATURES

- High-speed cutting stroke with precision-ground guides
- Sturdy, fully enclosed body for durability.
- Guillotine Type Cutting System
- Manual lubrication pump for prolonged life.
- Air blower system integrated
- In - built Hydraulic Power Pack
- Electromagnetic Clutch
- False Clamp Facility
- Hand protection Electronic light safety bar and two hand cut start in-built
- Air cushioning on both table and side table
- High grade cast gears for long service life.
- Advanced control panel for ease of operation.
- Simple knife changing system.



TECHNICAL SPECIFICATIONS

Parameter	Specification
Cutting width	1000-1370 mm (will cut in both limits)
Cutting depth	1320 mm and above
Clamp opening (Min.)	165 mm
Smallest cut without false Clamp	27 mm (Maximum)
Number of Cuts per min	25 (minimum)
Maximum Clamp Pressure	40 kN (Minimum)
Motorized back guage with ball screw accuracy	within ± 5 mm maximum
Back guage advance Speed	15cm/sec (minimum)
Display type	TFT colour LED/LCD touch panel
External Communication	USB port
Memory Capacity	To store min of 100 jobs of 50 pages each
Input least count value	10 μ m

Manufactured by:

M.D. ENGINEERING WORKS

20/B, Ghanshyam Indl. Estate, B/s. Margha Farm, B/h. Shastri Stadium, Bapunagar,
Ahmedabad-380 024.

Mobile: 98981-42645.

E-mail: contact@microcut.co.in / microcutindia@hotmail.com **Website :** www.microcut.co.in